

03nov04 13:16:55 User015070 Session D10524.1
Sub account: HARD1.006A-CSP

FILE HARDFOR2.DOC

ENGLISH ABSTRACTS OF FOREIGN PATENTS

File 351:Derwent WPI 1963-2004/UD,UM &UP=200470
(c) 2004 Thomson Derwent

*File 351: For more current information, include File 331 in your search.
Enter HELP NEWS 331 for details.

Set Items Description

--- -----

?..exs td692

11/7/1

DIALOG(R)File 351:Derwent WPI

(c) 2004 Thomson Derwent. All rts. reserv.

007709587

WPI Acc No: 1988-343519/*198848*

Cement moulding for flooring verandas and balconies - comprises inorganic
lightweight aggregate upper layer and lower layer contg. reinforcing
fibre, pulp and fibrous mesh

Patent Assignee: SEKISUI CHEM IND CO LTD (SEKI)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 63257631	A	19881025	JP 8794190	A	19870416	198848 B

Priority Applications (No Type Date): JP 8794190 A 19870416

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 63257631	A		8		

Abstract (Basic): JP 63257631 A

A cement moulding comprises an upper layer contg. an inorganic
light wt. aggregate, and a lower layer contg. a reinforcing fibre and
pulp. In the lower layer, a fibrous mesh material is provided.

Pref. the cement moulding is obtd. by dehydration press moulding
using a metallic mould provided with water-discharge pores at the
moulding face. The inorganic light wt aggregate is Japanese shirasu,
Japanese Kokaseki, obsidian, or perlite. The reinforcing fibre has a
tensile modulus of elasticity of at least 3000 kg/sq.mm. The
reinforcing fibre is aramid fibre, vinylon fibre or carbon fibre. The
pulp is reproduced pulp and/or used paper pulp. The fibrous mesh
material has a tensile modulus of elasticity of at least 3000 kg/sq.mm;
and is aramid fibre, vinylon fibre or carbon fibre.

USE/ADVANTAGE - The cement moulding has superior light wt. and
high impact resistance. The moulding is harmless to human bodies.

Derwent Class: A93; L02; P73

International Patent Class (Additional): B32B-013/00